

1. A packet flow control apparatus performing flow control of packets each having variable length, comprising:

10 a counter means updated based on a rate
determined in accordance with a packet length
calculated by a counter value of the counter means and
limited flow of packets;

15 a sending order control means for
managing a sending order of each packet accumulated in
the buffer memory, and for sending a read instruction
of each packet to the buffer memory, based on the
sending time determined by the sending time determining
20 means;

wherein the sending time determining means includes a memory means storing parameters which can determine a state of change of the counter value of the counter means for each control unit to independently control packet flow; when an input packet is written into the buffer memory, the sending time determining means obtains the sending time of the input packet based on the parameter having the same control unit as the input packet read out from the memory

means; and the sending time determining means updates the parameters having the same control unit in the memory means based on a newly obtained sending time of the input packet, and transfers the newly obtained
5 sending time of the input packet to the sending order control means.

2. A packet flow control apparatus performing flow control of packets each having variable length comprising:

10 a buffer memory for temporarily accumulating arrived packets until a sending time for each packet;

a counter means updated based on a rate determined in accordance with a packet length
15 calculated by a counter value of the counter means and limited flow of packets;

a sending time determining means for determining the sending time of each packet based on the counter value and a present time; and

20 a sending order control means for managing a sending order of each packet accumulated in the buffer memory, and for sending a read instruction of each packet to the buffer memory, based on the sending time determined by the sending time determining
25 means;

wherein the sending time determining means includes a memory means storing parameters for each control unit to independently control the packet flow, which include a sending time of a pre-packet

0977440-020604

belonging to the control unit and a counter value at
the sending time; when an input packet is written into
the buffer memory, the sending time determining means
obtains the sending time of the input packet and the
5 counter value at the sending time, based on the
parameters having the same control unit as the input
packet read out from the memory means; and the sending
time determining means updates the parameters having
the same control unit in the memory means based on a
10 newly obtained sending time of the input packet and the
counter value at the sending time, and transfers the
newly obtained sending time of the input packet to the
sending order control means.

3. A packet flow control apparatus performing
15 flow control of packets each having variable length,
comprising:

a buffer memory for temporarily
accumulating arrived packets until a sending time for
each packet;
20 a counter means updated based on a rate
determined in accordance with a packet length
calculated by a counter value of the counter means and
limited flow of packets;

a sending time determining means for
25 determining the sending time of each packet based on
the counter value and a present time; and)

a sending order control means for
managing a sending order of each packet accumulated in
the buffer memory, and for sending a read instruction

0077340-000004

of each packet to the buffer memory, based on the sending time determined by the sending time determining means;

5 wherein the sending time determining means includes a memory means storing parameters for each control unit to independently control the packet flow, which include a recovery time to return the counter value at the sending time of a pre-packet belonging to the control unit, to a limit value; when
10 an input packet is written into the buffer memory, the sending time determining means obtains the sending time of the input packet and the recovery time to return the counter value at the sending time to the limit value, based on the parameters read out from the memory means;
15 and the sending time determining means updates the parameters having the same control unit in the memory means based on a newly obtained recovery time of the input packet, and transfers the newly obtained recovery time of the input packet to the sending order control
20 means.

4. A packet flow control apparatus performing flow control of packets each having variable length, comprising:

25 a buffer memory for temporarily accumulating arrived packets until a sending time for each packet;

 a counter means updated based on a rate determined in accordance with a packet length calculated by a counter value of the counter means and

097740-0000
T09000-04E2260

limited flow of packets;

a sending time determining means for determining the sending time of each packet based on the counter value and a present time; and

5 a sending order control means for managing a sending order of each packet accumulated in the buffer memory, and for sending a read instruction of each packet to the buffer memory, based on the sending time determined by the sending time determining means;

10 wherein the sending time determining means includes a memory means storing parameters which can determine a state of change of the counter value of the counter means for each control unit to

15 independently control packet flow; when a packet to be sent is read out from the buffer memory, the sending time determining means obtains the sending time of a next packet to be sent after next time within packets belonging to the control unit of the sending packets in

20 the buffer memory, based on the parameter having the same control unit as the sending packet read out from the memory means; and the sending time determining means updates the parameters having the same control unit in the memory means based on a newly obtained

25 sending time of a next packet, and transfers the newly obtained sending time of the next packet to the sending order control means.

5. A packet flow control apparatus performing flow control of packets each having variable length,

0977340-090901

a buffer memory for temporarily accumulating arrived packets until a sending time for each packet;

a sending time determining means for determining the sending time of each packet based on the counter value and a present time; and

wherein the sending time determining means includes a memory means storing parameters for each control unit to independently control the packet flow, which include a sending time of a packet belonging to the control unit and a counter value at the sending time; when a packet to be sent is read out from the buffer memory, the sending time determining means obtains the sending time of a next packet to be sent after next time within packets belonging to the control unit of the sending packets in the buffer memory and a counter value at the sending time, based on the parameter having the same control unit as the

wherein the sending time determining means includes a memory means storing parameters for each control unit to independently control the packet flow, which include a sending time of a packet belonging to the control unit and a counter value at the sending time; when a packet to be sent is read out from the buffer memory, the sending time determining means obtains the sending time of a next packet to be sent after next time within packets belonging to the control unit of the sending packets in the buffer memory and a counter value at the sending time, based on the parameter having the same control unit as the

5

10

15

20

25

a sending order control means for managing a sending order of each packet accumulated in the buffer memory, and for sending a read instruction of each packet to the buffer memory, based on the sending time determined by the sending time determining means;

wherein the sending time determining means includes a memory means storing parameters for each control unit to independently control the packet

09777340-090604

flow, which include a recovery time to return the counter value at the sending time of a packet belonging to the control unit to a limit value; when a packet to be sent is read out from the buffer memory, the sending time determining means obtains the sending time of a next packet to be sent after next time within packets belonging to the control unit of the sending packets in the buffer memory and the recovery time to return a limit value to a counter value at the sending time, based on the parameter having the same control unit as the sending packet read out from the memory means; and the sending time determining means updates the parameters having the same control unit in the memory means based on a newly obtained recovery time of a next packet, and transfers the newly obtained recovery time of the next packet to the sending order control means.

7. A packet flow control apparatus performing flow control of packets each having variable length, as claimed in claim 4, wherein, when there are no packets belonging to the control unit in the buffer memory for the control unit of the input packets, the sending time determining means determines the sending time of the input packet when the input packet is written into the buffer memory, and transfers the sending time to the sending order control means, and updates the parameters in the memory means based on the sending time.

8. A packet flow control apparatus performing flow control of packets each having variable length, as claimed in claim 5, wherein, when there are no packets

belonging to the control unit in the buffer memory for the control unit of the input packets, the sending time determining means determines the sending time of the input packet when the input packet is written into the buffer memory, and transfers the sending time to the sending order control means, and updates the parameters in the memory means based on the sending time.

9. A packet flow control apparatus performing flow control of packets each having variable length, as claimed in claim 6, wherein, when there are no packets belonging to the control unit in the buffer memory for the control unit of the input packets, the sending time determining means determines the sending time of the input packet when the input packet is written into the buffer memory, and transfers the sending time to the sending order control means, and updates the parameters in the memory means based on the sending time.

10. A packet flow control apparatus performing flow control of packets each having variable length, as claimed in any one of claims 1 to 9, wherein the parameters in the memory means are normalized based on a limited flow value, so as to set an update rate of the counter means to "1".

11. A packet flow control apparatus performing flow control of packets each having variable length, as claimed in any one of claims 1 to 9, wherein the sending order control means previously sorts the sending order of the packets accumulated in the buffer memory, based on the sending time information of the

packets received from the sending time determining means, into a sorting memory, and performs the read instruction to the buffer memory by searching the packets to be sent at the next time.

5 12. A packet flow control apparatus performing flow control of packets each having variable length, as claimed in any one of claims 1 to 9, wherein the sending order control means previously sorts the sending order of the packets accumulated in the buffer
10 memory by dividing a plurality of time zones, based on the sending time information of the packets received from the sending time determining means for each divided time zone, into the sorting memory, and performs the read instruction to the buffer memory by
15 searching the packets to be sent at the next time.

 13. A packet flow control apparatus performing flow control of packets each having variable length, as claimed in any one of claims 1 to 9, wherein, when the sending time determined by the sending order
20 determining means is large, the sending order control means temporarily stores the sending time to another memory different from the sorting memory, and sorts the sending time into the sorting memory before the sending time.

25 14. A packet flow control apparatus performing flow control of packets each having variable length, as claimed in any one of claims 1 to 9, wherein a priority order of each packet is added to each sorted information accumulated in the sorting memory of the

097340-00001

15. A packet flow control apparatus performing flow control of packets each having variable length, as claimed in any one of claims 1 to 9, wherein a packet length of each packet is added to each sorted information accumulated in the sorting memory of the sending order control means, and, when there are a plurality of packets to be sent at the same sending time zone, the packet having a shorter packet length is preferentially sent from the sorting memory.

a calculating means for calculating a sending timing of an input packet, using a counting means updated based on the information of the packet length of the input packet and the information of a limited flow set to the input packet; and

17. A method for controlling packet flow of packets each having variable length, the steps comprising:

5

10